

3/8" Compressed Air Line

- Hose terminates in 1/4" female threaded brass fittings
- Includes 1/4" high flow coupler and plug
- 300 psi max pressure



3/8" Compressed Air Line

| Model | NSN | Length | Price |
|------------|-----|--------|-------|
| 922-A06H10 | | 10 | |
| 922-A06H20 | | 20 | |
| 922-A06H30 | | 30 | |
| 922-A06H40 | | 40 | |
| 922-A06H50 | | 50 | |

1/2" Compressed Air Line

- Hose terminates in 1/2" male threaded brass fittings
- Includes 1/2" safety coupler and plug
- Safety coupler relieves line pressure before disconnecting
- 200 psi max pressure



1/2" Compressed Air Line

| Model | NSN | Length | Price |
|------------|-----|--------|-------|
| 922-A08H10 | | 10 | |
| 922-A08H20 | ▲ | 20 | |
| 922-A08H30 | | 30 | |
| 922-A08H40 | | 40 | |
| 922-A08H50 | ▲ | 50 | |
| 922-A08H60 | | 60 | |
| 922-A08H80 | | 80 | |

3/4" Compressed Air Line

- Hose terminates in 3/4" male threaded brass fittings
- Includes 3/4" safety coupler and plug
- Safety coupler relieves line pressure before disconnecting
- 200 psi max pressure



3/4" Compressed Air Line

| Model | NSN | Length | Price |
|------------|-----|--------|-------|
| 922-A12H10 | | 10 | |
| 922-A12H20 | | 20 | |
| 922-A12H30 | | 30 | |
| 922-A12H40 | | 40 | |
| 922-A12H60 | | 60 | |
| 922-A12H80 | | 80 | |

★ Available on GSA Advantage website @ www.GSAadvantage.gov
 ▲ This item has an NSN - See Model / NSN table on page 4.

Conductive Compressed Air Line

For use in explosive dust and gas atmospheres, these air lines feature conductive hose and all non-sparking brass and stainless steel fittings.

3/8" Conductive Compressed Air Line

- Hose terminates in 1/4" male threaded brass fittings
- Includes 1/4" all brass high flow coupler and plug
- 300 psi max pressure

3/8" Compressed Air Line Conductive

| Model | NSN | Length | Price |
|----------------|-----|--------|-------|
| 922-A06H10-EXP | | 10 | |
| 922-A06H20-EXP | | 20 | |
| 922-A06H30-EXP | | 30 | |
| 922-A06H40-EXP | | 40 | |
| 922-A06H50-EXP | | 50 | |



1/2" Conductive Compressed Air Line

- Hose terminates in 1/2" male threaded brass fittings
- Includes 1/2" all stainless steel coupler and plug
- 300 psi max pressure

1/2" Compressed Air Line Conductive

| Model | NSN | Length | Price |
|----------------|-----|--------|-------|
| 922-A08H10-EXP | | 10 | |
| 922-A08H20-EXP | | 20 | |
| 922-A08H30-EXP | | 30 | |
| 922-A08H40-EXP | | 40 | |
| 922-A08H50-EXP | | 50 | |



Compressed Air Line by the Foot

Get the same compressed airline we use, a la carte.

Compressed Air Line by the Foot

| Model | NSN | Diameter | Rating | Price |
|---------------|-----|----------|---------|-------|
| 922-H04PV-YL | | 1/4" | 300 psi | |
| 922-H06PV-YL | | 3/8" | 300 psi | |
| 922-H08PV-BL | | 1/2" | 200 psi | |
| 922-H12PV-RD | | 3/4" | 200 psi | |
| 922-H16PV-RD | | 1" | 200 psi | |
| 922-H06CD-RD* | | 3/8" | 300 psi | |
| 922-H08CD-RD* | | 1/2" | 200 psi | |

* = Conductive



- ★ Available on GSA Advantage website @ www.GSAadvantage.gov
- ▲ This item has an NSN - See Model / NSN table on page 4.