



Universal Cutoff Saw Shrouds (sold with or without grinder)

A grip on the top of the shroud aids in precise cuts. This puts your control above and in line with the cutting edge, making the tool much easier to control and more ergonomic. In addition, the grinder and shroud pivot independently, keeping the shroud flat on the work surface while the grinder pivots with your hand.

Every shroud includes: mandrel, 2' x 1" hose whip, and swivel adapter for connection to 1" vacuum hose. Refer to hose and fitting section for other hose adapters.

Features

- Fits ANY tool with a 1/4" collet – straight or right angle sanders, grinders, etc.
- Accepts discs with 1/4" arbor hole
- Precision finished anodized aluminum housing
- Positive Lock hose fitting – hoses won't pull free
- Built in depth control with graduation marks, provides precise adjustment
- Ergonomic comfort grip molded into shroud
- Works with the grinders you already own - NO MODIFICATIONS REQUIRED
- Recommended tool speed: 20,000 - 23,000 RPM – Max tool speed: 25,000 RPM



2" Universal Cutoff Saw Shroud (50mm)

Model	NSN	Grinder	Orientation	Motor RPM	Motor HP (W)	Air Inlet ID inch (mm)	Weight lbs (kg)	Price
674-A2032		Not Included	-	-	-	-	-	
690-72032-01R		Dotco 12L1281-36	Right Angle	20,000	0.3	1/4"		
690-72032-01S		Dotco 12L2580-01	Straight	23,000	0.9	1/4"		

3" Universal Cutoff Saw Shroud (75mm)

Model	NSN	Grinder	Orientation	Motor RPM	Motor HP (W)	Air Inlet ID inch (mm)	Weight lbs (kg)	Price
674-A2048		Not Included	-	-	-	-	-	
690-72048-01R		Dotco 12L1281-36	Right Angle	20,000	0.3	1/4"		
690-72048-01S		Dotco 12L2580-01	Straight	23,000	0.9	1/4"		

- ⚠ Never exceed the maximum operating speed of your abrasive.
- ★ Available on GSA Advantage website @ www.GSAadvantage.gov
- ★ This item has an NSN - See Model / NSN table on page 4.



Please call for other Tool & Shroud combinations that may be available.