



Universal Drill Shroud (sold with or without drill)

This Universal Shroud design attaches between the drill and chuck and provides exceptional dust collection when used on composites or sheet metal. The shroud works with drill bits, reamers, and countersinks.

Every shroud includes: 1" x 2' vacuum hose whip, 2 interchangeable lexan tips, and swivel adapter for connection to 1" vacuum hoses. Refer to hose and fitting section for other hose adapters.

Features

- Fits non-reversing drills with a 3/8"-24 threaded chuck
- Precision finished anodized aluminum housing
- Crystal Clear Lexan shroud does not obscure visibility (includes 2 sizes)
- Works with the drills you already own, up to 25,000 rpm
- Works with microstop countersinks up to 1.70" OD
- Removable/Replaceable Lexan shroud
- Positive Lock hose fitting – hoses won't pull free
- Shroud swivels freely around chuck, so the hose can be repositioned
- Shroud self centers on drill bit without the need for any expensive bushings
- Built-in depth control



Please call for other Tool & Shroud combinations that may be available.



Universal Drill Shroud

Model	NSN	Chuck Size	Drill	Orientation	Motor RPM	Motor HP (W)	Air Inlet ID inch (mm)	Weight lbs (kg)	Price
674-A3005		-	Not Included	-	-	-	-	-	
690-73004-01		3/8"	Dotco 14CNL92-51	Pistol Grip	3,200	0.5 (373)	1/4"	2.5 (1.1)	
690-73004-02		3/8"	Dotco 14CSL95-51	Pistol Grip	1,300		1/4"		
690-73004-03		1/4"	Dotco 14CFS93-38	Pistol Grip	3,200		1/4"		
690-73004-04		3/8"	Dotco 14CSL92-51	Pistol Grip	3,200	0.6	1/4"		
690-73004-20		3/8"	Ingersoll Rand 728LA2	Pistol Grip	2,850	0.9 (670)	1/4"	2.4 (1.0)	

- ⚠ Never exceed the maximum operating speed of your abrasive.
- ★ Available on GSA Advantage website @ www.GSAadvantage.gov
- ⚡ This item has an NSN - See Model / NSN table on page 4.