



Microstop Countersink Shroud (sold with or without drill)

Precise and clean – the Vacuum Microstop Countersink lets you perform precise, measured operations on sheet metal and composites without the danger of dust inhalation and FOD. The solid footplate ensures straight and steady motion, and the microstop makes adjustments a breeze.

Every shroud includes: 3/4" x 2' vacuum hose whip, and swivel adapter for connection to 1" or 3/4" vacuum hoses.

Features

- Upper and lower ball bearings for maximum spindle support
- Precision finished black oxide steel housing
- Shroud does not obscure visibility
- Shroud swivels freely around shaft, so the hose can be repositioned with ease
- Positive Lock hose fitting – hoses won't pull free
- Unique design pulls air and dust through and across the work surface
- Works with the drills you already own, up to 10,000 rpm - NO MODIFICATIONS REQUIRED

5/8" Microstop Countersink Shroud

Model	NSN	GSA	Cutter Capacity	Chuck Size	Hose Cuff ID inch (mm)	Drill	Orientation	Motor RPM	Motor HP (W)	Air Inlet ID inch (mm)	Weight lbs (kg)	Price
674-A1116			5/8"	-	3/4" or 1"	Not Included	-	-	-	-	-	
690-71116		★	5/8"	3/8"	3/4" or 1"	Dotco 14CSL95-51	Pistol Grip	1,300	0.6 (450)	1/4"	2.9 (1.3)	

⚠ Never exceed the maximum operating speed of your abrasive.



Please call for other Tool & Shroud combinations that may be available.