



Universal Radial Shrouds (sold with or without grinder)

Designed for 3M Bristle Discs or cut off wheels, this shroud does not obscure the working edge of the abrasive, so users can easily see the work surface.

Every shroud includes: mandrel, 2' x 1" hose whip and swivel adapter for connection to 1" vacuum hoses. Refer to hose and fitting section for other hose adapters.

Features

- Fits ANY tool with a 1/4" collet – straight or right angle sanders, grinders, routers, etc.
- Shroud does not obscure visibility
- Shroud swivels freely around shaft, so the hose can be repositioned with ease
- Works with the grinders you already own, up to 25,000 rpm - NO MODIFICATIONS REQUIRED
- Positive Lock hose fitting – hoses won't pull free
- Accepts up to 4 bristle discs with 3/8" center hole



3" Radial Shroud Narrow (1-2 bristle discs or 1 cutoff wheel 75mm)

Model	NSN	Grinder	Orientation	Motor RPM	Motor HP (W)	Air Inlet ID inch (mm)	Weight lbs (kg)	Price
674-A1648		Not Included	-	-	-	-	-	
674-A1648-02R		Dotco 12L1280-36	Right Angle	12,000	0.3 (220)	1/4"	1.1 (0.5)	
674-A1648-03S		Dotco 12L2082-01	Straight	18,000	0.6 (448)	1/4"	1.4 (0.6)	

3" Radial Shroud Wide (2-4 bristle discs 75mm)

Model	NSN	Grinder	Orientation	Motor RPM	Motor HP (W)	Air Inlet ID inch (mm)	Weight lbs (kg)	Price
674-A2148		Not Included	-	-	-	-	-	
674-A2148-02R		Dotco 12L1280-36	Right Angle	12,000	0.3 (220)	1/4"	1.1 (0.5)	
674-A2148-03S		Dotco 12L2082-01	Straight	18,000	0.6 (448)	1/4"	1.4 (0.6)	

4" Radial Shroud Wide (1 cutoff wheel 100mm)

Model	NSN	Grinder	Orientation	Motor RPM	Motor HP (W)	Air Inlet ID inch (mm)	Weight lbs (kg)	Price
674-A1664		Not Included	-	-	-	-	-	
674-A1664-02R		Dotco 12L1280-36	Right Angle	12,000	0.3 (220)	1/4"	1.1 (0.5)	
674-A1664-03S		Dotco 12L2082-01	Straight	18,000	0.6 (448)	1/4"	1.4 (0.6)	

- ⚠ Never exceed the maximum operating speed of your abrasive.
- ★ Available on GSA Advantage website @ www.GSAadvantage.gov
- ✦ This item has an NSN - See Model / NSN table on page 4.